

POUSSE SERINGUE 02 VOIES AVEC ECRAN LCD

POUSSE SERINGUE 02 VOIES AVEC ECRAN LCD MARQUE STARCARE



Syringes	5ml, 10ml, 20ml, 30ml, 50(60)ml		
Flow Rate Range	5ml : 0.1ml/h~150ml/h 10ml : 0.1ml/h~300ml/h 20ml : 0.1ml/h~400ml/h 30ml : 0.1ml/h~600ml/h 50ml : 0.1ml/h~1200ml/h		
Flow Rate Step	0.1ml/h		
Flow Rate Accuracy	±2% (including Mechanic Accuracy±1%)		
Volume Limit	0.1~9999.9 ml		
Purge Rate	5ml : 150ml/h ; 10ml : 300ml/h ; 20ml : 600ml/h 30ml : 900ml/h ; 50ml : 1200ml/h		
BOLUS	5ml : 10ml/h~150ml/h 30ml : 10ml/h~600ml/h	10ml : 10ml/h~300ml/h 50ml : 10ml/h~1200ml/h	20ml : 10ml/h~400ml/h
Syringe Modes	Flow Rate,Time/Volume,Drug/Weight,BOLUS		
KVO	0.1~5ml/h		
Occlusion Alarm	3-level sensitivities setting		
Audio & Visual Alarm	Finished, Barrel clasp,Plunger Head,Pause Overtime,Near Empty ,Empty, Battery Low, Battery run out,Motor reverse, Incorrect parameters setting, System failure ,Occlusion , AC lost etc.		
Drug Library	Upgradable		
Wireless Monitoring	Upgradable		
Display	Two 2.8In TFT		
Power Source	≤25W, 85V ~ 265V , 50Hz/60Hz		
Battery	DC12V , 2000mAh (double chunnel last 4 hours at 5ml/hr after fully recharged)		
Operation Condition	Temperature: +5°C ~ +40°C, Relative Humidity ≤80% , Atmospheric Pressure 70KPa ~ 106Kpa		
Dimensions	356mmX 192mmX 134mm		
Weight	3.2kg		